



# 102" SLICK 360 SPECIFICATIONS

|             |                                                                                                             |
|-------------|-------------------------------------------------------------------------------------------------------------|
| WINGSPAN    | 102"                                                                                                        |
| FUSE LENGTH | 101" (WITH RUDDER + SPINNER)<br>90" (WITH SPINNER, WITHOUT RUDDER)<br>83" (WITHOUT SPINNER, WITHOUT RUDDER) |
| WEIGHT      | 26-28 LBS                                                                                                   |
| HEIGHT      | 30" (GROUND TO CANOPY HIGH POINT)<br>27" (GROUND TO TOP OF RUDDER)                                          |

RECOMMENDED EQUIPMENT:

- 100-120CC GAS ENGINE (DA-120, GP-123, ETC.)
- 25MM STANDOFF (APEX/DUALSKY ALUMINUM ENGINE MOUNT)
- QTY. 7 STANDARD SIZE SERVOS (MINIMUM 600 OZ. IN. TORQUE), QTY. 1 STANDARD SIZE THROTTLE SERVO
- 27-29" CARBON FIBER PROP (28X9.5, 27X11 RECOMMENDED)
- 10-20 CHANNEL RADIO AND RECEIVER SETUP

SERVO ARM SETUP:

- QTY. 4 1.5" APEX ALUMINUM CLAMPING STYLE M3 ARMS (AILERONS)
- QTY. 3 2.0" APEX ALUMINUM CLAMPING STYLE M3 ARMS (ELEVATOR AND RUDDER)
- QTY. 1 1.25" APEX ALUMINUM CLAMPING STYLE M3 ARM (THROTTLE)

CONTROL SURFACE SETUP:

| SURFACE  | HIGH RATES                              | LOW RATES  |
|----------|-----------------------------------------|------------|
| AILERON  | 38 DEG. UP, 37 DEG. DOWN<br>50-55% EXPO | 20 DEGREES |
| ELEVATOR | 55-60 DEGREES<br>50-55% EXPO            | 15 DEGREES |
| RUDDER   | MAX WITHOUT BINDING<br>45-55% EXPO      | 20 DEGREES |

COVERING (MANUFACTURED BY FLFRG)

- ORANGE ("BANSHEE")

-022-1 ORANGE

-014-1 WHITE

-016-1 SILVER

-015-1 BLACK

-027-1 IRON GREY
- RED/BLUE ("APEX")

-009-2 RED

-014-1 WHITE

-030-1 PEARL BLUE

-016-1 SILVER

