



60" SLICK 360 SPECIFICATIONS

WINGSPAN	60"
FUSE LENGTH	63" (WITH RUDDER + SPINNER) 56" (WITH SPINNER, WITHOUT RUDDER)
WEIGHT	6-6.5 LBS (WITH BATTERY)

RECOMMENDED EQUIPMENT/PNP EQUIPMENT:

- DUALSKY GA-1500R MOTOR
- APEX/DUALSKY SUMMIT 120A ESC
- APEX/DUALSKY 16X7E CARBON FIBER PROP
- THETA/APEX THM988 HV SERVOS
- 6S 4000MAH 100C BATTERY (NOT INCLUDED WITH PNP)
- 6-CHANNEL RX (NOT INCLUDED WITH PNP)

SERVO ARM SETUP:

- QTY. 2 1.0" APEX ALUMINUM CLAMPING STYLE ARMS (AILERONS)
- QTY. 2 1.25" APEX ALUMINUM CLAMPING STYLE ARMS (ELEVATOR AND RUDDER)

CONTROL SURFACE SETUP:

SURFACE	HIGH RATES	LOW RATES
AILERON	38 DEG. UP, 37 DEG. DOWN 50-55% EXPO	20 DEGREES
ELEVATOR	55-60 DEGREES 50-55% EXPO	15 DEGREES
RUDDER	MAX WITHOUT BINDING 45-55% EXPO	20 DEGREES

COVERING (MANUFACTURED BY FLFRC)

- ORANGE ("BANSHEE")

-022-1 ORANGE

-014-1 WHITE

-016-1 SILVER

-015-1 BLACK

-027-1 IRON GREY
- RED/BLUE ("APEX")

-009-2 RED

-014-1 WHITE

-030-1 PEARL BLUE

-016-1 SILVER

